



# Ultra V Timberguard

## POLYURETHANE

Product Code 220-4780, 220-4781, 220-4782, 220-4783

Issue No. 1

Date: 20<sup>th</sup> Aug 2008

Ultra V Timberguard is a tough, hard, chemically resistant long life coating designed to give extended durability, enhanced appearance and serviceability to exterior / interior wood products.

### About The Product:

- Single pack water based
- Lacquer dry
- Suitable for timber
- Tintable

### Surfaces:

- Timber & Composite timber
- Parquet flooring
- Decking
- Cladding
- Furniture
- Fibro Cement

**Colour:** Clear

**Pigment:** Transparent Oxides

**Sheen:** Gloss and Matt

**Toxicity:** Lead free, non toxic when dry.

### Drying Time:

- 30 minutes hard dry @ 25°C
- Recoat with itself no less than 2 hours depending on temperature and other weather conditions.

**Volume Solids:** 32%

**Weight Solids:** 35%

**Container Volume:** 1, 4, 10, & 20 Litres

### Coverage:

Depending on the surface profile of the timber and the application technique the following can be considered as a guide.

### **Dressed Timbers:**

Approximately 12m<sup>2</sup> to 16m<sup>2</sup> per litre

### **Sawn Timber:**

Approximately 10m<sup>2</sup> to 12m<sup>2</sup> per litre

### UV Protection:

State of the art UV absorbers are incorporated to assist in surface protection from the effects of sunlight & is resistant to yellowing and age crazing.

### Surface Preparation:

### Previously Coated Surfaces:

Refer to the product label for surface preparation details of previously coated surfaces and for full details refer to web site: [www.ultravgroup.com.au](http://www.ultravgroup.com.au)

### New Surfaces:

- All surfaces must be clean and dry
- New timber should be allowed to weather for approx 6 weeks
- Use a suitable timber wash to remove tannins and waxes such as **Exterior Timber Prep.**

### Application:

The first application on rough sawn timber can be thinned to a maximum of 10% and a further 2 coats applied without thinning.

Dressed timber should have a minimum of 2 coats applied not thinned.

Refer to web site for full details [www.ultravgroup.com.au](http://www.ultravgroup.com.au)

### Applicators:

Apply by brush, roller, flat lambs wool applicator, spray gun.

### Additional:

**Stepongrit** anti slip grit may be added to this product for improved grip of foot traffic to W rating for wet surfaces as per **AS/NZS 4586 – 2004**

**Clean Up:** Tap water

**Flammability:** Non Flammable

### Chemical Resistance:

Timberguard has good resistance to household products such as beer, coffee, tea, wine, cola, solvents etc

### Safety and Environment:

- Keep out of the reach of children
- Ensure adequate ventilation during use and drying
- Refer Material Safety Data Sheet for full information
- Do not pour paint products down sewers or stormwater drains
- Dispose of unused paint and containers through special collection services
- Contact your local council for information about disposal

### First Aid

#### **If swallowed:**

- Do not induce vomiting
- Drink plenty of water
- Seek medical advice

#### **If in eyes:**

- Flood eyes with water for 15 minutes.
- If irritation persists seek medical attention

To obtain a Material Safety Data Sheet contact:-

Ultra V Group Customer Service  
Tel: 03 98748913

Fax: 03 98748914

Email: [info@ultravgroup.com.au](mailto:info@ultravgroup.com.au)

**Disclaimer:** The information in this data sheet is believed to be as up to date as possible. No responsibility is accepted or warranty given or implied since the application procedures are outside the control of the company.